








Polyfilm Polyplex Polyester Films

Type: CF120 high clarity PET film 50my

Polyfilm Ultra Clear CF grade Polyester film is designed as base film for high clarity packaging and industrial applications. One side is chemically treated for improved slip and handelability. Treated surface is suitable for adhesion to solvent based inks and coatings.

Composition



-  chemical treatment
-  standard surface
-  core
-  standard surface

treatment

CF120 = chemically treated side inside

Typical Properties

Provisional data

Property	Units	Nominal	Method	Conditions
Mechanical Properties				
Nominal thickness	μ	50	Polypex Method	
Yield	m^2/kg	14.3	Polypex Method	
Unit weight	g/m^2	70		
Density	g/cm^3	1.4		
Elongation at break	MD %	160	ASTM D-882	
	TD %	145		
Tensile strength	MD kg/cm^2	1900	ASTM D-882	
	TD kg/cm^2	2000		

Property	Units		Nominal	Method	Conditions
Thermal Properties					
Heat shrinkage	MD	%	1.6	ASTM D-1204	150 Deg. C/30 minutes
	TD	%	0.2		
Surface Properties					
Co-efficient of friction static			0.45	ASTM D-1894	
Co-efficient of friction dynamic			0.35	ASTM D-1894	
Optical Properties					
Haze		%	0.8	ASTM D-1003	

Standard Roll Presentation

Thickness μ	Core mm	Length m	outside diameter mm
50	76	3000	460
50	152	4500	585
50	152	6000	665

Disclaimer

The information given above is to the best of our knowledge and experience at the time of printing. We make no warranty, express or implied, for specific product properties or as to the fitness of the product for any specific use or purpose. The above data is purely for reader's consideration, investigation and verification and should be read in conjunction with the general conditions for sale.

Edition: 8/2008